Appln. No. 10/697,943 Amd. dated July 12, 2007

Reply to Office Action of: May 8, 2007

## Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

1. (Currently Amended) A sampling device for obtaining samples of internal body substances in the digestive tract of a patient, said device having a shape of a swallowable capsule (2) which allows a sample of the body substance to enter the capsule through at least one inlet opening (18) which is opened in a predetermined position of the digestive tract following contact with the body substance to be collected,

members, a cap member (4) and a body member (6), which are permanently joined to each other,

a capsule wall (3) comprising said inlet opening (18), which initially is sealed and, when the patient has swallowed the capsule (2), is opened in said predetermined position following contact with the body substance to be collected,

an inner chamber (5), defined by said capsule wall (3) and disposed to preserve a vacuum or underpressure relative to the environment when the inlet opening (18) is sealed, and

Appln. No. 10/697,943 Amd. dated July 12, 2007

Reply to Office Action of: May 8, 2007

a blocking member (12) disposed in within the inner chamber (5) adjacent to the inlet opening (18) in the capsule wall (3), said blocking member (12) being elastic and having a configuration, such that, when the inlet opening (18) has been opened following contact with said body substance, the blocking member (12) has a flow permitting configuration which admits a flow of body substance into the inner chamber (5) as long as a there is a pressure difference between the inner chamber (5) and the external environment of the capsule (2) and a flow preventing configuration which blocks the inlet opening (18) from the inside of the chamber (5) when said pressure difference has been equalised by the flow of body substance into the capsule (2).

- 2. (Original) A sampling device according to claim

  1, characterised in that the inlet opening (18) is sealed by a plug member (20) of a material that is dissolved following contact with said body substance.
- 3. (Original) A sampling device according to claim

  1, characterised in that the blocking member (12) consists of
  an elastic, self-sealing membrane, which in said flow
  preventing configuration sealingly bears on the inside of the
  capsule wall (3), such that an outflow of the body substance
  in the inner chamber (5) is prevented.

Appln. No. 10/697,943 Amd. dated July 12, 2007 Reply to Office Action of: May 8, 2007

- 4. (Currently Amended) A sampling device according to claim 3, characterised in that the capsule (2) comprises two members, a cap member (4) and a body member (6), which are permanently joined to each other, and that said blocking member (12) is elamped retained in the capsule wall (3) between said cap member (4) and said body member (6).
- 5. (Previously Presented) A sampling device according to claim 4, **characterised** in that the blocking member (12) is bell-shaped and has at least one laterally located aperture (16) for a through-flow of body substance into the inner chamber (5).
- 6. (Original) A sampling device according to claim 5, characterised in that a peripheral edge of the blocking member (12) is clamped between said cap member (4) and said body member (6).
- 7. (Original) A sampling device according to claim 2, characterised in that the plug member (20) consists of two or more layers of different materials and that each layer is dissolved in different positions in the digestive tract following contact with a specific body substance.
- 8. (Original) A sampling device according to claim 4, characterised in that a filter (10) is clamped between said

Appln. No. 10/697,943 Amd. dated July 12, 2007

Reply to Office Action of: May 8, 2007

cap member (4) and said body member (6) for filtrating the body substance that flows into the inner chamber (5).

9. (Original) A sampling device according to any of the preceding claims, **characterised** in that protrusions (30) are disposed externally on the capsule (2) circumferentially of the inlet opening (18), thereby forming inlet grooves (32) between the protrusions (30) for securing a free flow of body substance to the inlet opening (18).

Claims 10-19 (Cancelled).